



Operating temperature -30~+40°C




i Integrated LED (COB)

n°	Power Volt	W	(u/h)	(° K)	Ra v	(cd)	(lm)	(°)	(%)	Colour	IP	★ ENERGY ★		
1 MM 05431	230	10.5	25000	3000	80	-	800	110	NO	BLACK	66	A+	IN	66
1 MM 05410	230	10.5	25000	4000	80	-	800	110	NO	BLACK	66	A+	IN	66
1 MM 05289	230	10.5	25000	4000	80	-	800	110	NO	WHITE	66	A+	IN	66
1 MM 05412	230	10.5	25000	4000	80	-	800	110	NO	GREY	66	A+	IN	66
2 MM 05415	230	10.5	25000	4000	80	-	800	110	NO	BLACK	66	A+	IN	66
2 MM 05291	230	10.5	25000	4000	80	-	800	110	NO	WHITE	66	A+	IN	66
2 MM 05416	230	10.5	25000	4000	80	-	800	110	NO	GREY	66	A+	IN	66

Fonda with sensor

1 MM 06943	230	11,5	25000	4000	80	-	1250	110	NO	WHITE	66	A+	IN	MO	66
1 MM 06945	230	11,5	25000	4000	80	-	1250	110	NO	BLACK	66	A+	IN	MO	66



m	Lux	Ø cm
0.5	1280	143
1	320	286
1.5	142	428
2	80	571

Beam angle = 110°

