



Life in Light

MEGAMAN®










SPIRAL

Model No.:
Voltage (V):
Wattage (W):

SP0405
220-240
5.0



lightplus
 A bright vision on light

Lamp Base	Lamp Life (hrs)	Diameter (mm)	Length (mm)	Lumen Output (lm)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 60% of the Full Light Output (sec)	Switching Cycles (times)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
					CRI	PF			 x 7 times		
Warm White (2700K)											
E14	10,000	32	89	270	≥82	≥0.55	<1.5	<15	50,000	≥76%	A
E27	10,000	32	85	270	≥82	≥0.55	<1.5	<15	50,000	≥76%	A
B22	10,000	32	82	270	≥82	≥0.55	<1.5	<15	50,000	≥76%	A
Cool White (4000K)											
E14	10,000	32	89	270	≥82	≥0.55	<1.5	<15	50,000	≥76%	A
E27	10,000	32	85	270	≥82	≥0.55	<1.5	<15	50,000	≥76%	A
Day Light (6500K)											
E14	10,000	32	89	250	≥80	≥0.55	<1.5	<15	50,000	≥76%	A
E27	10,000	32	85	250	≥80	≥0.55	<1.5	<15	50,000	≥76%	A
B22	10,000	32	82	250	≥80	≥0.55	<1.5	<15	50,000	≥76%	A



Life in Light





MEGAMAN®

SPIRAL

Model No.: **SP0405**
Voltage (V): **220-240**
Wattage (W): **5.0**



lightplus
A bright vision on light

-  Operating Temperature (°C) : **-10 to +40**
-  Mercury Content (mg): **2.0**
-  Clean-up Procedures in Case of Lamp Breakage: www.megaman.cc/clean-up
-  Disposing of Lamp at its End of Life: www.megaman.cc/disposal

