

**LED GX53**

Model No.: LR2205
Voltage (V): 220-240
Rated Wattage (W): 5.0



lightplus
 A bright vision on light

| Lamp Base | Rated Lamp Life (hrs) | Diameter (mm) | Length (mm) | Rated Luminous Flux (lm) | Colour Rendering Index (Ra) | Power Factor | Starting Time (sec) | Warm-up Time Up to 100% of the Full Light Output (sec) | Switching Cycles (times) | Lumen Maintenance at the End of Lamp Life (%) | Energy Label (EEL) |
|---------------------------|-----------------------|---------------|-------------|--------------------------|-----------------------------|--------------|---------------------|--|--------------------------|---|--------------------|
| | | | | | CRI | PF | | | | | |
| Warm White (2800K) | | | | | | | | | | | |
| GX53 | 15,000 | 75 | 24 | 300 | 80 | >0.5 | <0.5 | Instant full light | >1,000,000 | ≥70 | A+ |
| Cool White (4000K) | | | | | | | | | | | |
| GX53 | 15,000 | 75 | 24 | 300 | 80 | >0.5 | <0.5 | Instant full light | >1,000,000 | ≥70 | A+ |
| Day Light (6500K) | | | | | | | | | | | |
| GX53 | 15,000 | 75 | 24 | 300 | 80 | >0.5 | <0.5 | Instant full light | >1,000,000 | ≥70 | A+ |



Operating Temperature (°C) :

-30 to +40



Mercury Content (mg):

N/A

