Life in Light

MEGAMAN®

LED PAR20

Model No.: LR2906-WFL
Voltage (V): 220-240
Rated Wattage (W): 6.0

lightplus
A bright vision on light

Lamp Base	Rated Lamp Life (hrs)	Diameter (mm)	Length (mm)	Total Luminous Flux (lm)	Rated Luminous Flux in 90° cone (lm)	Rated Beam Angle (°)	Max. Luminous Intensity (cd)	Colour Rending Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 100% of the Full Light Output(sec)	Switching Cycles (times)	Colour Consistency (SDCM)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
				lm	Φ_{use}		cd	CRI	PF			x ? times	SDCM		
Warm White (2800K)															
E27	15,000	63	90	350	250	35	450	80	>0.5	<0.5	Instant full light	>1,000,000	<6	≥70	A

Operating Temperature (℃) : -30 to +40

Mercury Content (mg): N/A

Spectral power distribution

2800K





LED PAR20

Conventional PAR20

Copyright © MEGAMAN® 2014. All rights reserved.

The rated lamp life, rated luminous flux in 90° cone, total luminous flux, rated beam angle and rated wattage are equivalent to their nominal values, which show on the product packaging.
There is no measurable output from 180nm to 380nm, so the chart shows only 380nm to 800nm.
All information stated in this document is valid at the time of update and is subject to change without prior notice.
Any form of reproduction or further transmission of any portion of this document is prohibited.